

RACING





FANTIC, THE FAMOUS ITALIAN BRAND THAT MADE OFF-ROAD HISTORY, REVOLUTIONISES ITS ENDURO/MOTARD RANGE DEDICATED TO YOUNG PEOPLE.

A completely new, **100% Racing - inspired** design combined with numerous technical upgrades make our **50 and 125 models** top of the line.

These are further complemented by the **250cc trail** enduro version, thde perfect combination of power and ease of riding while having fun.







50 CC -ROOKIE OF THE

YEAR.

Who says rookies don't deserve the best? The all new XE 50 MY23 is even more inspired by the world champion XE125: 100% racing design, new graphics and air filter that can be changed in a flash thanks to the side flap. Even the engine does not suffer from shyness, the only 50cc 2t euro5 in the world is a concentrate of technology and performance 100% made in Italy.









MOTOR	
ENGINE	Single cylinder 2 stroke, Euro5, liquid cooled
CYLINDER	48,9 cc
CARBURETOR	DellOrto ø16 mm
BORE	40,3 mm Stroke: 39 mm
FUEL INTAKE	Membrane
IGNITION	Electronic, variable
STARTER	Kick starter
GEARBOX	6 gears with multidisc in oil clutch
EXHAUST	Manifold and muffler Euro5 by BigOne
CHASSIS	
FRAME	Perimeter in steel
SUB FRAME	Removable in steel
SWINGARM	Steel, progressive link
TIRES	80/90x21 - 110/80x18
WHEELS	Aluminium, anodised black and CNC hubs
BRAKES	Front disc "Wave" ø260mm – Rear disc "Wave" ø220mm
TRIPLE CLAMPS	Aluminium
FRONT SUSPENSION	FANTIC FRS ø41mm USD
REAR SUSPENSION	Mono FANTIC FRS- 1 regulation
HANDLEBARS	Steel, ø22mm
LIGHT	
REAR	Full LED
FRONT	halogen Lights
TURNING LIGHTS	Led Front&Rear
DIMENSION	
LENGHT	2100 mm
SEAT HEIGHT	910 mm
WHEELBASE	1420 mm
WEIGHT	94 kg
FUEL TANK	Capacità 7,5 l













THE GYM OF NEW CHAMPION.

The factory feeling of the XEF MY23 is even more evident in the design, which proudly recalls our victorious racing range. Close kinship also on the technical side, with a new rear end with side access to the air filter. a guarantee of reliability and high Indispensable on the race track, it makes routine maintenance even

easier. XEF 125 is agility, racing soul and freedom on every terrain combined with the fantastic and technological 125cc 4t e5 Minarelli engine, a reference in its category: performance.









MOTOR	
ENGINE	Single cylinder 4 strokes Euro5, liquid cooled
MAXIMUM POWER	11 kW (15 PS) to 9.750 rpm
MAXIMUM TORQUE	11,8 Nm to 6.750 rpm
DISPLACEMENT	124,66 cc
BORE	52 mm
STROKE	58,7 mm
DISTRIBUTION	SOHC 4-valve, Variable camshaft timing
IGNITION	Electronic
STARTER	Electric
GEARS	б
CLUTCH	Wet multidisc, back-torque limiter
EXHAUST	Manifold and muffler Euro5 by ARROW
CHASSIS	
FRAME	Perimeter frame steel CrMo
SUB FRAME	Removable in steel
SWINGARM	Steel, progressive link
TIRES	90/90x21 - 120/90x18
WHEELS	Aluminium, black anodized
BRAKES	Disc "Wave" ø260mm - Disc "Wave" ø220mm, combined brake system
TRIPLE CLAMPS	Forged aluminum
FRONT SUSPENSION	FANTIC ø41mm USD
REAR SUSPENSION	FANTIC 125 – preload regulation
HANDLEBARS	ø22 steel
LIGHT	
REAR	Full LED
FRONT	Full LED
TURNING LIGHTS	Led Front&Rear
DIMENSION	
LENGHT	2110 mm
SEAT HEIGHT	910 mm
WHEELBASE	1420 mm
WEIGHT	112 kg
FUEL TANK	Capacità 7,5 l













STRESS-FREE ENDURO

Just point to a spot on the horizon and our XEF 250 trail will get you there in no time, effortlessly and with maximum fun. Thanks to the new ultra-adjustable forks and cncmachined steering plates you'll have maximum feeling in all conditions, while the powerful 250cc euro5 will never leave you short of torque to jump one obstacle after another. The MY23 also brings with it a side access filter: quick and easy maintenance to minimise stops between trails.









MOTOR	
ENGINE	Single cylinder 4 strokes Euro5, liquid cooled
MAXIMUM POWER	15,8 kW (21,5 PS) to 8.750 rpm
MAXIMUM TORQUE	18,6 Nm to 6.750 rpm
DISPLACEMENT	249.6 cc
BORE	77 mm
STROKE	53.6 mm
DISTRIBUTION	SOHC 4-valve
IGNITION	Electronic
STARTER	Electric
GEARS	6
CLUTCH	Wet multidisc
EXHAUST	Manifold and muffler Euro5 by ARROW
CHASSIS	
FRAME	Perimeter frame steel CrMo
SUB FRAME	Removable in aluminium
SWINGARM	Aluminium, variable section and progressive link
TIRES	90/90x21 - 120/90x18
WHEELS	Aluminium, black anodized
BRAKES	Disc "Wave" ø260mm - Disc "Wave" ø220mm
TRIPLE CLAMPS	Aluminum, CNC racing triple clamps
FRONT SUSPENSION	FANTIC FRS ø43mm USD, racing setup, forged aluminium fork bottoms
REAR SUSPENSION	FANTIC FRS 125 Piggyback – preload and hydraulic regulation
HANDLEBARS	ø28 aluminum
LIGHT	
REAR	Full LED
FRONT	Full LED
TURNING LIGHTS	Led Front&Rear
DIMENSION	
LENGHT	2100 mm
SEAT HEIGHT	915 mm
WHEELBASE	1420 mm
WEIGHT	122 kg
FUEL TANK	Capacità 7,5 l











AGILE, SNAPPY AND EXTREMELY FUN.

«But is it really a 50cc?»

This is what everyone will ask you because the xm50 is an up and running bike: agile, nimble and extremely enjoyable.

Sleek suspension with

upside-down stems, CrMo chassis and the explosive Minarelli 50cc with 6 gears.









MOTOR	
ENGINE	Single cylinder 2 stroke, Euro5, liquid cooled
CYLINDER	48,9 cc
CARBURETOR	DellOrto ø16 mm
BORE	40,3 mm Stroke: 39 mm
FUEL INTAKE	Membrane
IGNITION	Electronic, variable
STARTER	Kick starter
GEARBOX	6 gears with multidisc in oil clutch
EXHAUST	Manifold and muffler Euro5 by BigOne
CHASSIS	
FRAME	Perimeter in steel CrMo
SUB FRAME	Removable in steel
SWINGARM	Steel, progressive link
TIRES	100/80x17 - 130/70x17
WHEELS	Aluminium, anodised black and CNC hubs
BRAKES	Front disc "Wave" ø260mm – Rear disc "Wave" ø220mm
TRIPLE CLAMPS	Aluminium
FRONT SUSPENSION	FANTIC FRS ø41mm USD
REAR SUSPENSION	Mono FANTIC FRS 50
HANDLEBARS	Steel, ø22mm
LIGHT	
REAR	Full LED
FRONT	halogen Lights
TURNING LIGHTS	Led Front&Rear
DIMENSION	
LENGHT	2040 mm
SEAT HEIGHT	870 mm
WHEELBASE	1420 mm
WEIGHT	95 kg
FUEL TANK	Capacità 7,5 l














TOP OF THE CATEGORY.

Top of the line.

A responsive, high-performance chassis to turn every ride into pure fun. An engine that needs no introduction: the minarelli 125 lc 4t is the most advanced in the sector,

with full-bodied power across the rpm range thanks to variable ignition timing. A tough act to beat at any karting track











MOTORENGINESingle cylinder 4 strokes EuroS, liquid cooledMAXIMUM POWER11 kW (15 PS) to 9.750 rpmMAXIMUM TORQUE11,8 Nm to 6.750 rpmDISPLACEMENT124.66 ccBORE52 mmSTROKE58,7 mmSTROKE58,7 mmDISTRIBUTIONSOHC 4-valve, Variable camshaft timingIGNITIONElectroincSTARTERElectroincEXAMPSManifold and muffler EuroS by ARROWCLUTCHWet multidisc, back torque limiterEXHAUSTManifold and muffler EuroS by ARROWCHASSISEverimeter frame steel CrMoSUB FRAMEPerimeter frame steel CrMoSUB FRAMESteel, progressive linkTIRES100/80X17-130/70x17WHEELSAluminium, black anodizedBRAKESDisc "Wave" ø320mm - Disc "Wave" ø220mm, combined brake systemTIRIEL CLAMPSFANTC 41mm USDRRAR SUSPENSIONFANTC 41mm USDRRAR SUSPENSIONFANTC 41mm USDRRARFull LEDFROMTHalogenTURNING LIGHTSEle Front&RearFROMTS10 mmFROMT110 mmSEAT HEIGHT870 mmWHEELBASE870 mmWHEELBASE870 mmWIEGHT112 kgFUE TANKGapacta 75 l		
MAXINUM POWER11 kW (15 PS) to 9.750 rpmMAXINUM TORUE11.8 Nm to 6.750 rpmDISPLACEMENT124,66 ccBORE52 mmSTROKE58,7 mmDISTRIBUTIONSOHC 4-valve, Variable canshaft timingIDISTRIBUTIONElectronicSTARTERElectronicGEARS6CLUTCHWet multidisc, back-torque limiterEXHAUSTManifold and muffler EuroS by ARROWCHASSISFrameFRAMEPerimeter frame steel CrMoSUB FRAMESteel, progressive linkTIRES100/80x17 - 130/70x17WHEELSAluminium, black anodizedBRAKESDisc "Wave" a320mm - Disc "Wave" a220mm, combined brake systemTIPLE CLAMPSForged aluminumFRONT SUSPENSIONFANTIC 241mm USDREARSUSPENSIONHANDLEBARSo22 steelLIGHTLENGHTREAR11 LEDFRONTHalogenTURNING LIGHTS210 mmSEAT HEIGHT320 mmKEIGHT112 kg	MOTOR	
MAXINUM TORQUE11,8 Nm to 6,750 rpmDISPLACEMENT124,66 ccBORE52 mmSTROKE58,7 mmDISTRIBUTIONSOHC 4-valve, Variable camshaft timingIDISTRIBUTIONElectronicSTARTERElectronicGEARS6CLUTCHWet multidisc, back-torque limiterEXHAUSTManifold and muffler Euros by ARBOWCHASSISVFRAMEPerimeter frame steel CrMoSUB FRAMERemovable in steelSWINGARMSteel, progressive linkTIRES100/80x17 - 130/70x17WHEELSJoisc "Wave" 320mm - Disc "Wave" o220mm, combined brake systemTRIPLE CLAMPSForged aluminumFRAMESourge aluminumFRONT SUSPENSIONFANTIC 24 num USDREARJuli LEDREARHalogenTURNING LIGHTSLed FrontaRearDIMENSIONZ10 mmFRONTLENGHTILENGHT210 mmSEAR SUSPENSION210 mmGEARS00 mmSUSPENSION210 mmFRAME210 mmFRAME210 mmSEAR SUSPENSION210 mmFRAME210 mmFRAME210 mmSUGHT210 mmSUGHT210 mmSURGHT210 mmSURGHT210 mmSURGHT210 mmSURGHT210 mmSURGHT210 mmSURGHT210 mmSURGHT210 mmSURGHT210 mm	ENGINE	Single cylinder 4 strokes Euro5, liquid cooled
DisPLACEMENT124,66 ccBORE52 mmSTROKE58,7 mmDISTRIBUTIONSOHC 4-valve, Variable camshaft timingIGNITONElectronicSTARTERElectronicGEARS6CLUTCHWet multidisc, back-torque limiterEXHAUSTManifol and muffler Euro's by ARROWCHASSISFRAMEPerimeter frame steel CrMoSUB FRAMERemovable in steelSWINGARMSteel, progressive linkTIRES100/80x17-130/70x17WHEELSJoisc "Wave" a320mm - Disc "Wave" a220mm, combined brake systemTRIPLE CLAMPSForged aluminumFRAMESorged aluminumFRANESitel, Progressive linkTRUE CLAMPSAUMINIC MATON 120WHELSAUMINIC MATON 120REAR SUSPENSIONFANTIC 26 - preload regulationTRUPL CLAMPSQ2 steelIEUHTILEDFRONT SUSPENSIONEd Front&RearFRONT SUSPENSIONAUTIC 125 - preload regulationTURNING LIGHTSQ2 steelIEUHTILEDFRONTILI EDFRONTILI EDFRONT210 mmSEAT HEIGHT320 mmSEGHT210 mmSEGHT12 kg	MAXIMUM POWER	11 kW (15 PS) to 9.750 rpm
BORE32 mmSTROKE58,7 mmDISTRIBUTIONSOHC4-valve, Variable camshaft timingIGNITIONElectronicSTARTERElectronicGEARS6CLUTCHWet multidisc, back-torque limiterEXHAUSTMolf and muffler EuroS by ARROWCHASSISFrameFRAMEPerimeter frame steel CrMoSUB FRAMESteel, progressive linkSUB GRAMSteel, progressive linkTIRES100/80x17-130/70x17WHEELSJoic "Wave" a320mm - Disc "Wave" a220mm, combined brake systemTRIPLE CLAMPSFANTIC 041mm USDREAR SUSPENSIONFANTIC 24-1mm USDREAR SUSPENSIONFANTIC 125 - preload regulationHADLEBARSGul LEDFRONTHalogenTURNING LIGHTSLed Front&RearDIMENSIONLed Front&RearFRONTHalogenTURNING LIGHTS110 mmSEAR MERS110 mmSEAR	MAXIMUM TORQUE	11,8 Nm to 6.750 rpm
STROKE58,7 mmDISTRIBUTIONSOHC 4-valve, Variable camshaft timingIGNITIONElectronicSTARTERElectronicGEARS6CLUTCHWet multidisc, back-torque limiterEXHAUSTManifold and muffler EuroS by ARROWCHASSISEFRAMEPerimeter frame steel CrMoSUB FRAMERemovable in steelSWINGARMSteel, progressive linkTIRES100/80x17 - 130/70x17WHEELSNaminum, black anodizedBRAKESDisc "Wave" a020mm - Disc "Wave" a020mm, combined brake systemTRIPLE CLAMPSFANTIC 401mm USDREAR SUSPENSIONFANTIC 25 - preload regulationHANDLEBARSSul 2 steelIGHTILEDTURNING LIGHTSHalogenTURNING LIGHTS210 nmmSEAT HEIGHT370 nmWHEELBASE370 nmWIELBASE112 g	DISPLACEMENT	124,66 cc
DistributionSOHC 4-valve, Variable camshaft timingDistributionSOHC 4-valve, Variable camshaft timingIGNITIONElectronicSTARTERElectronicGEARS6CLUTCHWet multidisc, back-torque limiterEXHAUSTManifold and muffler EuroS by ARROWCHASSISFRAMEFRAMEPerimeter frame steel CrMoSUB FRAMERemovable in steelSWINGARMSteel, progressive linkTIRES100/80x17-130/70x17WHEELSAluminium, black anodizedBRAKESDisc "Wave" a020mm - Disc "Wave" a020mm, combined brake systemTRIPLE CLAMPSForged aluminumFRONT SUSPENSIONFANTIC 25 – preload regulationHANDLEBARSa02 steelLIGHTLIEDREARFull LEDREARHalogenTURNING LIGHTSLientot&RearLINGHT2110 mmSEAT HEIGHT870 mmWHEELBASE132 kg	BORE	52 mm
IGNITION Electronic STARTER Electronic GEARS 6 CLUTCH Wet multidisc, back-torque limiter EXHAUST Manifold and muffler EuroS by ARROW CHASSIS FRAME FRAME Perimeter frame steel CrMo SUB FRAME Removable in steel SWINGARM Steel, progressive link TIRES 100/80x17 - 130/70x17 WHEELS Aluminium, black anodized BRAKES Disc "Wave" a320mm - Disc "Wave" a220mm, combined brake system TRIPLE CLAMPS Forged aluminum FRONT SUSPENSION FANTIC 25 - preload regulation HANDLEBARS a22 steel LIGHT Halogen TURNING LIGHTS Led Front&Rear DIMENSION 210 mm ELENGHT 370 mm SEAT HEIGHT 870 mm WHEELBASE 112 kg	STROKE	58,7 mm
STARTERElectricGEARS6CLUTCHWet multidisc, back-torque limiterEXHAUSTManifold and muffler EuroS by ARROWCHASSISErimeter frame steel CrMoSUB FRAMERemovable in steelSWINGARMSteel, progressive linkTIRES100/80x17-130/70x17WHEELSAluminium, black anodizedBRAKESDisc "Wave" ø320mm - Disc "Wave" ø220mm, combined brake systemTRIPLE CLAMPSFORged aluminumFRONT SUSPENSIONFANTIC ø41mm USDREAR SUSPENSIONS2 steelLIGHTLalogenTRINIG LIGHTSLed Front&RearDIMENSIONLed Front&RearEARAJ10 mmSEAR HEIGHT\$70 mmWHEELBASE1435 mmWIELBASE12 kg	DISTRIBUTION	SOHC 4-valve, Variable camshaft timing
Brance Brance GEARS 6 CLUTCH Wet multidisc, back-torque limiter EXHAUST Manifold and muffler EuroS by ARROW CHASSIS E FRAME Perimeter frame steel CrMo SUB FRAME Removable in steel SWINGARM Steel, progressive link TIRES 100/80x17-130/70x17 WHEELS Aluminium, black anodized BRAKES Disc "Wave" ø320mm - Disc "Wave" ø220mm, combined brake system TRIPLE CLAMPS Forged aluminum FRONT SUSPENSION FANTIC 401mm USD REAR SUSPENSION FANTIC 25 - preload regulation HANDLEBARS 022 steel ILIGHT Ed Front& Rear FRONT Halogen TURNING LIGHTS Led Front&Rear DIMENSION Ed Front&Rear DIMENSION S70 mm SEAT HEIGHT 1435 mm WHEELBASE 1435 mm	IGNITION	Electronic
CLUTCH Wet multidisc, back-torque limiter EXHAUST Manifold and muffler EuroS by ARROW CHASSIS FRAME FRAME Perimeter frame steel CrMo SUB FRAME Removable in steel SWINGARM Steel, progressive link TIRES 100/80x17 - 130/70x17 WHEELS Aluminium, black anodized BRAKES Disc "Wave" ø320mm - Disc "Wave" ø220mm, combined brake system TRIPLE CLAMPS Forged aluminum FRONT SUSPENSION FANTIC ø41mm USD REAR SUSPENSION FANTIC 125 – preload regulation HANDLEBARS ø22 steel LIGHT Full LED TRONT SUSPENSION Full LED REAR Full LED FRONT Led Front&Rear JURNING LIGHTS Led Front&Rear DIMENSION S10 mm SEAT HEIGHT 110 mm SEAT HEIGHT 112 sg	STARTER	Electric
EXHAUSTManifold and muffler EuroS by ARROWCHASSISFRAMEPerimeter frame steel CrMoSUB FRAMERemovable in steelSWINGARMSteel, progressive linkTIRES100/80x17-130/70x17WHEELSAluminium, black anodizedBRAKESDisc "Wave" ø320mm - Disc "Wave" ø220mm, combined brake systemTRIPLE CLAMPSForged aluminumFRONT SUSPENSIONFANTIC ø41mm USDREAR SUSPENSIONFANTIC 125 - preload regulationHANDLEBARSø22 steelLIGHTLIDREARFull LEDFRONTLed Front&RearDIMENSIONLed Front&RearELROHT210 nmSEAT HEIGHT110 nmSEAT HEIGHT1435 nmWHEELBASE1435 nmWIELBASE112 kg	GEARS	6
CHASSIS FRAME Perimeter frame steel CrMo SUB FRAME Removable in steel SWINGARM Steel, progressive link TIRES 100/80x17 - 130/70x17 WHEELS Aluminium, black anodized BRAKES Disc "Wave" ø320mm - Disc "Wave" ø220mm, combined brake system TIPLE CLAMPS Forged aluminum FRONT SUSPENSION FANTIC ø41mm USD REAR SUSPENSION FANTIC 125 – preload regulation HANDLEBARS ø22 steel LIGHT REAR TURNING LIGHTS Led Front&Rear PIULED Led Front&Rear DIMENSION \$70 mm LENGHT 1435 mm WHEELBASE 142 g	CLUTCH	Wet multidisc, back-torque limiter
FRAMEPerimeter frame steel CrMoSUB FRAMERemovable in steelSWINGARMSteel, progressive linkTIRES100/80x17-130/70x17WHEELSAluminium, black anodizedBRAKESDisc "Wave" ø320mm - Disc "Wave" ø220mm, combined brake systemTRIPLE CLAMPSForged aluminumFRONT SUSPENSIONFANTIC ø41mm USDREAR SUSPENSIONFANTIC 125 - preload regulationHANDLEBARSo22 steelCIGHTIL IEDREARSul LEDFRONTHalogenTURNING LIGHTS101 mmSEAT HEIGHT\$70 mmSHENSION112 gm	EXHAUST	Manifold and muffler Euro5 by ARROW
SUB FRAMERemovable in steelSWINGARMSteel, progressive linkTIRES100/80x17-130/70x17WHEELSAluminium, black anodizedBRAKESDisc "Wave" ø320mm - Disc "Wave" ø220mm, combined brake systemTRIPLE CLAMPSForged aluminumFRONT SUSPENSIONFANTIC ø41mm USDREAR SUSPENSIONFANTIC 125 – preload regulationHANDLEBARS022 steelIGHTILIEDREARFull LEDFRONTLadgenTURNING LIGHTSLed Front&RearLINGHT110 mmSEAT HEIGHT370 mmWHEELBASE132 kg	CHASSIS	
swingarmsteel, progressive linkswingarmSteel, progressive linktitles100/80x17-130/70x17wheelsAluminium, black anodizedBRAKESDisc "Wave" ø320mm - Disc "Wave" ø220mm, combined brake systemtriple cLAMPSForged aluminumtriple cLAMPSForged aluminumFRONT SUSPENSIONFANTIC ø41mm USDREAR SUSPENSIONFANTIC ø41mm USDREAR SUSPENSIONFANTIC 125 – preload regulationHANDLEBARSø22 steelLIGHTLed Front& HalogenTURNING LIGHTSLed Front&RearDIMENSION2110 mmSEAT HEIGHT930 mmWHEELBASE132 smmWIGHT112 kg	FRAME	Perimeter frame steel CrMo
TIRES100/80x17-130/70x17WHEELSAluminium, black anodizedBRAKESDisc "Wave" ø320mm - Disc "Wave" ø220mm, combined brake systemTRIPLE CLAMPSForged aluminumFRONT SUSPENSIONFANTIC ø41mm USDREAR SUSPENSIONFANTIC 125 – preload regulationHANDLEBARSø22 steelLIGHTEREARFUI LEDTURNING LIGHTSLed Front&RearDIMENSION2110 mmSEAT HEIGHT970 mmWHEELBASE112 kg	SUB FRAME	Removable in steel
WHEELSAluminium, black anodizedBRAKESDisc "Wave" ø320mm - Disc "Wave" ø220mm, combined brake systemTRIPLE CLAMPSForged aluminumFRONT SUSPENSIONFANTIC ø41mm USDREAR SUSPENSIONFANTIC 125 – preload regulationHANDLEBARSø22 steelLIGHTLENGRTREARFUI LEDFRONTLed Front&RearDIMENSION2110 mmSEAT HEIGHT370 mmWHEELBASE112 kg	SWINGARM	Steel, progressive link
BRAKESDisc "Wave" ø320mm - Disc "Wave" ø220mm, combined brake systemBRAKESDisc "Wave" ø320mm - Disc "Wave" ø220mm, combined brake systemTRIPLE CLAMPSForged aluminumFRONT SUSPENSIONFANTIC ø41mm USDREAR SUSPENSIONFANTIC 125 – preload regulationHANDLEBARSø22 steelLIGHTHalogenTURNING LIGHTSLed Front&RearDIMENSION2110 mmSEAT HEIGHT970 mmWHEELBASE112 kg	TIRES	100/80x17 - 130/70x17
TRIPLE CLAMPSForged aluminumFRONT SUSPENSIONFANTIC ø41mm USDREAR SUSPENSIONFANTIC 125 - preload regulationHANDLEBARSø22 steelLIGHTIteDREARFull LEDFRONTHalogenTURNING LIGHTSLed Front&RearDIMENSION2110 mmSEAT HEIGHT870 mmWHEELBASE112 kg	WHEELS	Aluminium, black anodized
FRONT SUSPENSIONFANTIC ø41mm USDREAR SUSPENSIONFANTIC 125 - preload regulationHANDLEBARSø22 steelLIGHTIREARFull LEDFRONTHalogenTURNING LIGHTSLed Front&RearDIMENSIONILENGHT2110 mmSEAT HEIGHT870 mmWHEELBASE1435 mmWIGHT112 kg	BRAKES	Disc "Wave" ø320mm - Disc "Wave" ø220mm, combined brake system
REAR SUSPENSIONFANTIC 125 – preload regulationHANDLEBARSø22 steelLIGHTFull LEDREARFull LEDTURNING LIGHTSLed Front&RearDIMENSION2110 mmELENGHT870 mmWHEELBASE1435 mmWEIGHT112 kg	TRIPLE CLAMPS	Forged aluminum
HANDLEBARSø22 stelLIGHTFRARREARFull LEDTURNING LIGHTSLed Front&RearDIMENSION110 mmSEAT HEIGHT870 mmWHEELBASE1435 mmWEIGHT112 kg	FRONT SUSPENSION	FANTIC ø41mm USD
LIGHT REAR Full LED FRONT Halogen TURNING LIGHTS Led Front&Rear DIMENSION 2110 mm SEAT HEIGHT 870 mm WHEELBASE 1435 mm WEIGHT 112 kg	REAR SUSPENSION	FANTIC 125 – preload regulation
REARFull LEDFRONTHalogenTURNING LIGHTSLed Front&RearDIMENSION110 mmSEAT HEIGHT870 mmWHEELBASE1435 mmWEIGHT112 kg	HANDLEBARS	ø22 steel
FRONTHalogenTURNING LIGHTSLed Front&RearDIMENSION110 mmEARGHT2110 mmSEAT HEIGHT870 mmWHEELBASE1435 mmWEIGHT112 kg	LIGHT	
TURNING LIGHTS Led Front&Rear DIMENSION 2110 mm SEAT HEIGHT 870 mm WHEELBASE 1435 mm WEIGHT 112 kg	REAR	Full LED
DIMENSION LENGHT 2110 mm SEAT HEIGHT 870 mm WHEELBASE 1435 mm WEIGHT 112 kg	FRONT	Halogen
LENGHT 2110 mm SEAT HEIGHT 870 mm WHEELBASE 1435 mm WEIGHT 112 kg	TURNING LIGHTS	Led Front&Rear
SEAT HEIGHT 870 mm WHEELBASE 1435 mm WEIGHT 112 kg	DIMENSION	
WHEELBASE 1435 mm WEIGHT 112 kg	LENGHT	2110 mm
WEIGHT 112 kg	SEAT HEIGHT	870 mm
	WHEELBASE	1435 mm
FUEL TANK Capacità 7,5 l	WEIGHT	112 kg
	FUEL TANK	Capacità 7,5 l













XE50









XEF125





COMPETITION WHITE VERSION



XEF250







XM50





COMPETITION WHITE VERSION





XMF125









ESSENCE () F R D N G

FANTIC.COM









@FanticMotorOfficial

Gfanticmotor

Fantic Motor

@fanticmotor_official

FANTIC MOTOR S.P.A.

Via Tarantelli, 7 31030 Dosson di Casier (TV) ITALY info@fanticmotor.it



The vehicle images shown are for reference and may differ in some detail from production models. Data relating to specification, appearance, operation, weight and dimension is not binding and is subject to typographical, typesetting and printing errors. Modifications may be made without prior notice.